

according to Regulation (EC) No 1907/2006
Revision date: 09.07.2021 Revision No: 1,03

Date of printing: 07.07.2022
Page: 1 / 8

SilaPress Vario Liquid

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier**
Commercial product name: SilaPress Vario Liquid
Product group: Liquid component
- 1.2 Relevant identified uses of the substance or mixture and uses advised against**
Use of the substance/mixture: Manufacture of dental products.
- 1.3 Details of the supplier of the safety data sheet**
Manufacturer: retec® Kunststofftechnik GmbH
Street / mailbox: Industriestraße 2
Country code. / postal code / city: D-61191 Rosbach v.d.H
Phone: +49 (0) 6007 - 9157 0
Fax: +49 (0) 6007 - 9157 29
E-mail / Website: info@retec-dent.de / www.retec-dent.de
Contact person: Herr Dr. Manfred Steinbach
e-mail: manfred.steinbach@retec-dent.de
- Supplier:** SILADENT Dr. Böhme & Schöps GmbH
Street / mailbox: Im Klei 26
Country code. / postal code / city: D - 38644 Goslar
Phone: 0 53 21 / 37 79 – 0
Fax: 0 53 21 / 38 96 32
E-mail / Website: info@siladent.de / www.siladent.de
- 1.4 Emergency telephone number:** +49 (0) 6007-91570

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture:**
Regulation (EC) No. 1272/2008
Hazard categories:
Flammable liquid: Flam. Liq. 2
Skin corrosion/irritation: Skin Irrit. 2
Respiratory or skin sensitisation: Skin Sens. 1
Specific target organ toxicity - single exposure: STOT SE 3
Hazard Statements:
Highly flammable liquid and vapour.
Causes skin irritation.
May cause an allergic skin reaction.
May cause respiratory irritation.
- 2.2 Label elements:**
Regulation (EC) No. 1272/2008
Hazard components for labelling: Methyl methacrylate
1,4-Butandiol dimethacrylate
- Signal word:** Danger

Pictograms:



according to Regulation (EC) No 1907/2006
 Revision date: 09.07.2021 Revision No: 1,03

Date of printing: 07.07.2022
 Page: 2 / 8

SilaPress Vario Liquid

Hazard statements:

H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H335 May cause respiratory irritation.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 P302+P352 IF ON SKIN: Wash with plenty of water and soap.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P370+P378 In case of fire: Use carbon dioxide (CO₂), foam or dry powder to extinguish.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/container to as hazardous waste - in accordance with local and national legislation - suitable, approved incinerator for combustible organic waste.

2.3 Other hazards No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical characterisation: Mixture based on methyl methacrylate.

CAS No	Chemical name	Quantity
	EC No Index No REACH No	
	GHS Classification	
80-62-6	Methyl methacrylate	90 - < 95 %
	201-297-1 01-2119452498-28	
	Flam. Liq. 1, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H224 H315 H317 H335	
2082-81-7	1,4-Butandiol dimethacrylate	5 - < 10 %
	218-218-1 01-2119967415-30	
	Skin Sens. 1; H317	

Full text of H- and EUH-phrases: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
80-62-6	201-297-1	Methyl methacrylate	90 - < 95 %
	inhalation: LC50 = 29,8 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg		
2082-81-7	218-218-1	1,4-Butandiol dimethacrylate	5 - < 10 %
	dermal: LD50 = > 3000 mg/kg; oral: LD50 = > 10000 mg/kg		

SECTION 4: First aid measures

4.1 Description of first aid measures:

General information:

Remove contaminated, saturated clothing immediately. If skin irritation or rash occurs, get medical advice/attention. If eye irritation persists, get medical advice/attention.

After inhalation:

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

according to Regulation (EC) No 1907/2006
 Revision date: 09.07.2021 Revision No: 1,03

Date of printing: 07.07.2022

Page: 3 / 8

SilaPress Vario Liquid

After contact with skin:	After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In case of skin irritation, consult a physician.
After contact with eyes:	After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
After ingestion:	Do NOT induce vomiting. Rinse mouth. Call a physician immediately.
4.2 Most important symptoms and effects, both acute and delayed:	Causes skin irritation. May cause respiratory irritation. May cause an allergic skin reaction.
4.3 Indication of any immediate medical attention and special treatment needed:	Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media:	Carbon dioxide (CO ₂), Foam, Extinguishing powder.
Suitable extinguishing media:	
Unsuitable extinguishing media:	Full water jet.
5.2 Special hazards arising from the substance or mixture:	Highly flammable liquid and vapour. Can polymerise exothermically if heated, exposed to air, sunlight or by addition of free radical initiators. Vapours can form explosive mixtures with air
5.3 Advice for firefighters:	Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.
Additional information:	Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:	Remove all sources of ignition. Wear protective gloves and eye / face protection. Avoid inhalation of vapours. See section: 8.
6.2 Environmental precautions:	Do not allow to enter into surface water or drains.
6.3 Methods and material for containment and cleaning up:	Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.
6.4 Reference to other sections:	Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling:	
Advice on safe handling:	When using do not eat, drink, smoke, sniff. Use only in well-

according to Regulation (EC) No 1907/2006
 Revision date: 09.07.2021 Revision No: 1,03

Date of printing: 07.07.2022
 Page: 4 / 8

SilaPress Vario Liquid

Advice on protection against fire and explosion:

ventilated areas. Do not breathe gas/fumes/vapour/spray. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in headspace of closed systems. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Further information on handling:

Caution! Transport usually takes place at temperatures above the flash point.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:

Keep container tightly closed. Keep in a cool, well-ventilated place. Protect from direct sunlight.

Advice on storage compatibility:

Do not store together with: Material, oxygen-rich, Oxidising. Pyrophoric or self-heating substances.

Further information on storage conditions:

Keep away from heat.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
80-62-6	Methyl methacrylate			
	Worker DNEL, long-term	inhalation		208 mg/m ³
	Worker DNEL, long-term	dermal		17 mg/kg bw/day

8.2 Exposure controls:

Appropriate engineering controls:

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures:

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection:

Wear eye/face protection.

Hand protection:

To protect against splashes: butyl; EN 374.
 To protect against immersion: butyl; 0.7 mm or thicker, EN 374.
 The suitability of gloves should be agreed with the manufacturer. In the event of contamination or if the Breakthrough time is exceeded, change gloves. Resistance of the glove material: see information from the glove manufacturer.

Skin protection:

Flame-retardant protective clothing. Wear anti-static footwear and clothing.

according to Regulation (EC) No 1907/2006
 Revision date: 09.07.2021 Revision No: 1,03

Date of printing: 07.07.2022
 Page: 5 / 8

SilaPress Vario Liquid

Respiratory protection:

Wear suitable respiratory protection if technical measures are inadequate or not in place and exposure is to be expected that exceeds the DNEL (derived exposure level below which the substance does not cause any harm to human health). A suitable breathing mask with filter type A (EN141 or EN405) is recommended. A self-contained breathing apparatus may be necessary if particularly high vapour concentrations are formed.

SECTION 9: Physical and chemical properties

9.1	Information on basic physical and chemical properties	
	Physical state:	liquid
	Colour:	colourless
	Odour:	characteristic
	pH-Value:	not determined
	Changes in the physical state:	
	Melting point:	-48 °C
	Boiling point or initial boiling point and boiling range:	100,5 °C
	Flash point:	10 °C
	Flammability	
	Solid:	not applicable
	Gas:	not applicable
	Lower explosion limits:	2,1 vol. %
	Upper explosion limits:	12,5 vol. %
	Ignition temperature:	421 °C
	Auto-ignition temperature:	
	Solid:	not applicable
	Gas:	not applicable
	Decomposition temperature:	not determined
	Oxidizing properties	Not oxidizing.
	Vapour pressure:	
	(at 20 °C)	36 hPa
	Density (at 15,5 °C):	0,949 g/cm ³
	Water solubility:	
	(at 20 °C)	12,5 g/L
	Solubility in other solvents:	not determined
	Partition coefficient:	1,38
	Viscosity / dynamic (at 20 °C):	
		0,53 mPa·s
	Vapour density (at 20 °C):	3,5
	Evaporation rate:	not determined
9.2	Other information	
	Solid content:	not determined

SECTION 10: Stability and reactivity

10.1	Reactivity:	Highly flammable, Vapours can form explosive mixtures with air.
10.2	Chemical stability:	The product is stable under storage at normal ambient temperatures.
10.3	Possibility of hazardous reactions:	Can polymerise exothermically if heated, exposed to air, sunlight or by addition of free radical initiators.
10.4	Conditions to avoid:	Keep away from sources of heat (e.g. hot surfaces), sparks

according to Regulation (EC) No 1907/2006
 Revision date: 09.07.2021 Revision No: 1,03

Date of printing: 07.07.2022

Page: 6 / 8

SilaPress Vario Liquid

and open flames. Can polymerise exothermically if heated, exposed to air, sunlight or by addition of free radical initiators. Protect from direct sunlight.

10.5 Incompatible materials:

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

10.6 Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1 Information on toxicological effects:****Acute toxicity:**

Based on available data, the classification criteria are not met.

ATEmix tested

LD50, oral

LD50, dermal

LC50, inhalative (vapour) (4h)

Dose

7870 mg/kg

> 5000 mg/kg

78 mg/l

Species

Rat

Rabbit

Rat

Source

CAS No	Chemical name	Exposure routes	Dose	Species	Source	Method
80-62-6	Methyl methacrylate	oral	LD50 >5000 mg/kg	Rat	OECD 401	
		dermal	LD50 >5000 mg/kg	Rabbit		
		inhalative vapour	LC50 29,8 mg/l	Rat		
2082-81-7	1,4-Butandiol dimethacrylate	oral	LD50 >10000 mg/kg	Rat		
		dermal	LD50 >3000 mg/kg	Rabbit		

Irritation and corrosivity:

Causes skin irritation. Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects:

May cause an allergic skin reaction. (Methyl methacrylate; 1,4-Butandiol dimethacrylate)

Carcinogenic/mutagenic/toxic effects for reproduction:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause respiratory irritation. (Methyl methacrylate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Additional information on tests:

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

according to Regulation (EC) No 1907/2006
 Revision date: 09.07.2021 Revision No: 1,03

Date of printing: 07.07.2022
 Page: 7 / 8

SilaPress Vario Liquid

SECTION 12: Ecological information

12.1 Toxicity Acute (short-term) fish toxicity

CAS No	Chemical name				Species	Source	Method
	Aquatic toxicity	Dose	[h] [d]				
80-62-6	Methyl methacrylate						
	Acute fish toxicity	LC50 > 79mg/l	96 h		Oncorhynchus mykiss (Rainbow trout)	OECD 203	
	Acute algae toxicity	ErC50 > 110 mg/l	72 h		Selenastrum capricornutum	OECD 201	
	Acute crustacea toxicity	EC50 69 mg/l	48 h		Daphnia magna (Big water flea)	OECD 202	
	Crustacea toxicity	NOEC 37 mg/l	21 d		Daphnia magna (Big waterflea)	OECD 202	
2082-81-7	1,4-Butandiol dimethacrylate						
	Acute fish toxicity	LC50 32,5 mg/l	96 h		Oncorhynchus mykiss (Rainbow trout)		
	Acute crustacea toxicity	EC50 7,51 mg/l	48 h		Daphnia magna (Big water flea)	OECD 211	
	Crustacea toxicity	NOEC 7,51 mg/l			Selenastrum capricornutum		

12.2 Persistence and degradability: Biodegradable.

12.3 Bioaccumulative potential: On the basis of existing data about the elimination/degradation and bioaccumulation potential longer term damage to the environment is unlikely.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
80-62-6	Methyl methacrylate	1,38
2082-81-7	1,4-Butandiol dimethacrylate	3,1

12.4 Mobility in soil: Mobility in soil: No adsorption in soil or sediment.

12.5 Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6 Other adverse effects: No information available.

Further information: Avoid release to the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods:
Disposal recommendations: Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products:

070208: WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of plastics, synthetic rubber and man-made fibres; other still bottoms and reaction residues
 Classified as hazardous waste.

Contaminated packaging: Non-contaminated packages may be recycled. Handle

according to Regulation (EC) No 1907/2006
 Revision date: 09.07.2021 Revision No: 1,03

Date of printing: 07.07.2022
 Page: 8 / 8

SilaPress Vario Liquid

contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

<u>Land transport (ADR/RID):</u>	
14.1	UN number: UN 1247
14.2	UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED
14.3	Transport hazard class(es): 3
14.4	Packing group: II
	Hazard label: 3
	Classification code: F1
	Limited quantity: 1 L
	Excepted quantity: E2
	Transport category: 2
	Hazard No: 339
	Tunnel restriction code: D/E
	Other applicable information (land transport): SAPT: > 60 °C
<u>Inland waterways transport (ADN)</u>	
14.1	UN number: UN 1247
14.2	UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED
14.3	Transport hazard class(es): 3
14.4	Packing group: II
	Hazard label: 3
	Classification code: F1
	Limited quantity: 1 L
	Excepted quantity: E2
	Other applicable information (inland waterways transport): SAPT: > 60 °C
<u>Marine transport (IMDG)</u>	
14.1	UN number: UN 1247
14.2	UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED
14.3	Transport hazard class(es): 3
14.4	Packing group: II
	Hazard label: 3
	Special Provisions: -
	Limited quantity: 1 L
	Excepted quantity: E2
	EmS: F-E, S-D
	Other applicable information (marine transport): SAPT: > 60 °C
<u>Air transport (ICAO-TI/IATA-DGR)</u>	
14.1	UN number: UN 1247
14.2	UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED
14.3	Transport hazard class(es): 3
14.4	Packing group: II
	Hazard label: 3
	Limited quantity Passenger: 1 L
	Passenger LQ: Y-341
	Excepted quantity: E2
	IATA-packing instructions - Passenger: 353

according to Regulation (EC) No 1907/2006
 Revision date: 09.07.2021 Revision No: 1,03

Date of printing: 07.07.2022
 Page: 9 / 8

SilaPress Vario Liquid

IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L
Other applicable information (air transport)	SAPT: > 60 °C
14.5 Environmental hazards	
ENVIRONMENTALLY HAZARDOUS:	No
14.6 Special precautions for user	
Warning:	Combustible liquids.
14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture	
EU regulatory information	
Restrictions on use (REACH, annex XVII):	Entry 3
2010/75/EU (VOC):	90 % (854,1 g/l)
2004/42/EC (VOC):	90 % (854,1 g/l)
Information according to 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS
National regulatory information	
Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Water contaminating class (D):	1 - slightly water contaminating
Skin resorption/Sensitization:	Causes allergic hypersensitivity reactions.
15.2 Chemical safety assessment	Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

16.1 Abbreviations and acronyms	
ADR:	Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG:	International Maritime Code for Dangerous Goods
IATA:	International Air Transport Association
GHS:	Globally Harmonized System of Classification and Labelling of Chemicals
EINECS:	European Inventory of Existing Commercial Chemical Substances
ELINCS:	European List of Notified Chemical Substances
CAS	Chemical Abstracts Service
LC50:	Lethal concentration, 50%
LD50:	Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Skin Sens. 1; H317	Calculation method

according to Regulation (EC) No 1907/2006
Revision date: 09.07.2021 Revision No: 1,03

Date of printing: 07.07.2022
Page: 10 / 8

SilaPress Vario Liquid

STOT SE 3; H335	Calculation method
-----------------	--------------------

Relevant H and EUH statements (number and full text):

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

16.2 Further Information:

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)